

NVH-2524XRD

Video server 19", 4U, 24 bay HS, dual Xeon, SSD, RAID, RPSU

DESCRIPTION

The NVH-2524XRD series is a powerful, dual Xeon CPU rack-mountable VDG servers. It combines top quality components and a user-friendly configuration to deliver high-power output and reliability. It's casing and components are engineered to ensure an optimized airflow (even when stacked) for higher efficiency, which results in lower energy consumption. Its redundant hot-plug power supply ensures a continuous operation at all times.

FEATURES

4U Rack-mountable Server Chassis

Dual Xeon E5 CPU

24x 3.5" hot swappableHDD bays

Standard RAID 5configuration

875W Reduntant Hot-plug Power Supply

1x 24-Port 12G Mini-SAS HD Expander Backplane

Front access info tag for easy server management

Slide rail



Built as stand-alone server, the NVH-2524XRD's front-mounted hard-drives are configured for hot-swapping, as are the cooling fans, to ensure 24/7 operation. This means that they are easy to service and can reduce running costs.

The reliability is ensured through a standard RAID 5 configuration and redundancy, but can be configured otherwise if necessary. Optionally, a hot-standby hard-drive can be configured to ensure maximum reliability and reduce service needs. The NVH-2524XRD contains 24 slots for hard-disk storage.

Optional expansions:

- VDG Video server storage
- NVH-GBLAN for 1 extra Ethernet connection port
- Ethernet server adapter fiber

System	
Operating system	Microsoft Windows 10 Pro 64-bit
Hard disk	64GB SSD (included)
Recording storage capacity	Up to 288TB (3.5" hard disk drives)
Raid configuration	Standard Raid 5 configuration Except Raid 1 configuration with 2 hard drives
Effective recording storage capacity	276TB (after Raid 5)
Processors	2x Xeon E5 processor
Memory	32GB memory
Network Interface	Dual Gigabit Ethernet RJ-45 (10/100/1000 MB/s)
Interface Advanced Management Technology (AMT)	
Video output	VGA

Mechanical	
Form Factor	19-inch rackmount
Dimensions (DxWxH)	698mm x 432mm x 176mm (27.5" x 17" x 6.9")

Electrical	
Power Input	100-240VAC,50/60Hz,10-8A
Power Supply	875W Redundant hot-plug

Environmental	
Operating Temperature	5° C - 40° C (41°F - 104°F)
Storage Temperature	-40° C - 65° C (-40°F - 149°F)
Humidity	Non-Operating 50% to 90%, non-condensing with a maximum wet bulb of 28° C (at temperatures from

Ordering Info	
NVH-2524XRD	Video server 19", 4U, 24 bay HS, dual Xeon, SSD, RAID, RPSU

VDG Server accessories	
NVH-GBLAN	Extra 100/1000Mbps LAN interface
NVH-FIBER	Ethernet server adapter fiber

Basic video server storage	NVH-84TB	NVH-86TB	NVH-88TB	NVH-810TB
(incl. assembly and config)	4TB	6TB	8TB	10TB


Pro video server storage	NVH-92TB	NVH-94TB	NVH-96TB	NVH-98TB
(incl. assembly and config)	2TB	4TB	6TB	8TB

	NVH-910TB	NVH-912TB	NVH-914TB
	10TB	12TB	14TB









RELATED



Intel NVH-GBLAN

A PCI Express Ethernet adapter perfect for expanding your Ethernet port(s).



WesternDigital NVH Basic Server Storage

Basic server storage for the storage environments.



WesternDigital NVH Pro Server Storage

Professional server storage for the most demanding storage environments.
