




MOBILE-35/60 Mixing Power Amplifier

FEATURES

- Optional module slot (TP-100RDS, DMT-100)
- Easy-to-use amplifier for both mobile and fixed installation.
- balanced microphone inputs.
- Low & high pass tone control to increase intelligibility.
- Tel input terminal for tel night ringer.
- LED level meter.
- Over current protection.
- Three Mic inputs, two Aux & 1 Tape input.
- AC / DC (12V).
- Bass & treble control for pack series.

DRAWING



TECHNICAL SPECIFICATIONS

THD at 1kHz (Rated output)	MOBILE-35 : Less than 1% (25W) MOBILE-60 : Less than 1% (40W)
Output	REC : -6dB / 3K Ω Unbalanced
Input sensitivity impedance	MIC : -50dB/2K Ω BAL, TAPE : 0dB/3K Ω UNBAL AUX : -20dB/90K Ω (AUX1) BAL, -20dB/16K Ω (AUX2) BAL
Frequency response	Less than -3dB 150Hz~18kHz(at 1% THD)
Tone filter	Low 40Hz~400Hz -6dB/oct, High 2.5kHz~20kHz -6dB/oct
Power consumption	MOBILE-35 : 130W MOBILE-60 : 210W
Max curr. draw (120V/230V AC)	MOBILE-35 : 0.55A MOBILE-60 : 1A
Weight(kg)	MOBILE-35 : 6kg, MOBILE-60 : 7kg
Signal to Noise Ratio	AUX : More than 70dB MIC : More than 80dB
Power	AC230V/50Hz, DC12V
Dimensions(mm)	375(W) x 88(H) x 260(D)mm

MODULE SERIES (Option)

DMT-100
Digital Message & Timer Module



TP-100RDS
Digital RDS Tuner

